

TECHNICAL DATA SHEET

CAE153

PRODUCT NAME	Minerene
RESIN SUITABILITY	LLDPE,LDPE,MDPE,HDPE,PP
LIGHT FASTNESS	8.00
MIGRATION	5.00
HEAT STABILITY (MAX. °C)	300.00

Applications :

MinereneCAE153 is 72% content micro particle coated calcium carbonate masterbatch designs for extrusion sheet, blown film and woven bag applications. It exhibits good dilute ability together with optimum calcium carbonate dispersion characteristics.

Method of Addition :

MinereneCAE153 is designed for ease of dilution and homogeneous mixing and is therefore suitable for direct addition using automatic dosing units or by pre-blending.

Addition Rate :

The amount of masterbatch added depends on the performance requirements of the final application.

Packaging :

MinereneCAE153 is supplied in regular pellet form packed in 25 kg. bag and 1,000 kg. bulk bag. It should be stored in a dry place.

Storage :

Recommended storage life up to 1 year provided it is stored as directed.

Regulatory Status :

Raw materials used in this product comply with:

- CONEG 94/62/EC
- FDA 21 CFR part 178.3297 for colorants
- Food Contact Resolution AP(89)1
- RoHS Directive 2015/863
- Toy Standard EN71 Part 3

This product can be used only for the application as specified here above. Customer should inspect the product in order to satisfy itself as to the suitability of the product for the customer's particular purpose.