

# MATERIAL SAFETY DATA SHEET

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Code: AESB79

Product Description: Slip agent plus Anti block masterbatch

Manufacturer:

Salee Colour Public Company Limited.  
858 Moo 2 Soi 1C/1, Bangpoo Industrial Estate,  
Bangpoomai, Mueang Samutprakarn  
Samutprakarn 10280, Thailand.  
Tel. 662 323-2601-08 Fax: 662 323-2227-8

## 2. COMPOSITION INFORMATION ON INGREDIENTS

This product contains Slip agent and Anti-blocking agent dispersed in the plastic resin.

## 3. HAZARDS IDENTIFICATION

Experience in use this product is no hazardous.

## 4. FIRST-AID MEASURES

Eye Contact: Flush eyes with water if irritation occurs.

Skin contact: If contact with molten product occurs, treat as for thermal burn.

Ingestion: Not ordinarily required.

Inhalation: Not ordinarily required.

## 5. FIRE FIGHTING MEASURES

Extinguishing Media: Use water fog, foam, dry chemical or CO<sub>2</sub>

Special Protective Equipment for Fire Fighters: Material will not burn unless pre-heated. Do not enter fire space without full bunker gear (helmet with face shield, bunker coat, gloves and rubber boots: including a positive pressure NIOSH\* approved self-contained breathing apparatus. Cool fire exposed containers with water.

Unusual Fire and Explosion Hazards: Treat as a solid that can burn. Avoid accumulation and dispersion of dust to reduce explosion potential.

## 6. ACCIDENTAL RELEASE MEASURES

Methods for Cleaning Up: Shovel and sweep or use industrial vacuum cleaner. Avoid generating dust clouds. Put into containers for reclaiming or disposal as permitted by applicable national, state and local regulations. In the event of an uncontrolled release of this material, the user should determine if the released is reportable under applicable laws and regulations.

## **7. HANDLING AND STORAGE**

Handling: Treat as a solid that can burn. Adequate ventilation and / or engineering controls must be employed in high temperature processing to prevent exposure to potentially toxic/ irritating fumes. Bond and ground transfer equipment.

Storage: Store away from oxidizing materials, in a cool, dry place with adequate ventilation and absence of direct sunlight.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Respiratory Protection: Not ordinarily required.

Protective Clothing: Not ordinarily required.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

Density: 0.93 g/cc

Odor: None

Physical form: Granule

Flammability: Flammable

Flash Point: Not Applicable

## **10. STABILITY AND REACTIVITY**

Stability: Stable

Hazardous Polymerization: Will not occur

Materials to Avoid: Strong oxidizing agents

Condition to Avoid: Temperatures above 300 degree C

Hazardous Decomposition Products: At processing temperature , some degree of thermal degradation will occur.

## **11. TOXICOLOGICAL INFORMATION**

This product is none toxic.

## **12. ECOLOGICAL INFORMATION**

The material is not biodegradable. Avoid uncontrolled releases. If it enters a water course or sewer, advise proper authorities of possible floating polymer.

## **13. DISPOSAL CONSIDERATIONS**

All waste material should be packaged, labeled transported and disposed or reclaimed in conformance with applicable laws & regulations and in conformance with good engineering practices. Reclaim where possible.

## **14. TRANSPORT INFORMATION**

Department of Transportation Classification: None hazardous.

## **15. REGULATORY INFORMATION**

Not Applicable

## **16. OTHER INFORMATION**

*The information contained herein is based on current knowledge and experience; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customers, and the protection of the environment.*