

## Technical Data Sheet

### MEWH 14051

Property	Value	Method
Carrier resin	LLDPE	
Compatibility	LDPE, LLDPE, MDPE, HDPE, PP	
Density at 23°C (g/cm <sup>3</sup> )	1.96 ± 0.20	ASTM D 792

**Applications:** MEWH 14051 is 30% titanium dioxide pigment content masterbatch designs for blown film and general purpose application.

**Method of Addition:** MEWH 14051 is designed for ease of dilution and homogeneous mixing and is therefore suitable for direct addition using automatic dosing units or by pre-blending.

**Addition Rate:** The amount of masterbatch added depends on the performance requirements of the final application.

**Regulatory Status:** Raw materials used in this product comply with:

- Food Contact Resolution AP(89)1
- Toy Standard EN71 Part 3
- CONEG 94/62/EC
- RoHs Directive 2011/65/EC
- FDA 21 CFR 178.3297 Colorants for polymer

**Packaging:** MEWH 14051 is supplied in regular pellet form packed in 25 kg. that should be stored in a dry place at room temperature.

**Storage:** Recommended storage life up to 1 year provided it is stored as directed.

This product can be used only for the application as specified here above. Customer should inspect the product in order to satisfy itself as to the suitability of the product for the customer's particular purpose.